VOLVO



Volvo Electric Compact Excavators 2.68 - 2.78 t

ECR25 ELECTRIC

Volvo Construction Equipment

ECR25 ELECTRIC

Increase your uptime with this short swing radius electric compact excavator. All the power but none of the emissions as its diesel equivalent.



A compact game changer

The Volvo ECR25 Electric is a true game changer: the electric compact excavator takes a proven concept and then adds battery electric power. An electric model is perfect for working in limited spaces, because with no emissions there is no need for an exhaust extraction system. While getting the same performance as its diesel equivalent, you can recharge ECR25 Electric during your lunch and operate for four hours straight, wasting no time to refuel specifically.




Proven performance

- Same performance as its diesel equivalent
- Zero-tail swing radius
- Front corner stays within tracks width
- Great combined movements performance
- Range of Volvo Attachments



Flexible charging solutions

- Standard Electric Vehicles (EV) charging protocol
- Multiple charging options, gets to 80% in less than 1 hour
- Keep track of charging status, battery level and location with the Electric Machines Management Application



State-of-the-art battery technology

- 2 to 4 hours of run time depending on application
- Anti-theft fixed battery
- 48V lithium-ion, maintenance-free battery
- Designed to deliver up to 2 000 full charge cycles



Zero emission

- No emission locally
- Sound level down
- Low electricity cost
- No power consumption when machine not working



Reduced maintenance

- Maintenance-free electric motor with auto shutoff
- Easy access to components
- 50-hours greasing intervals
- Patented multifunction hydraulic filter, protecting the hydraulic system
- Hoses protected inside the boom and arm


Volvo ECR25 Electric in detail

Electrical system		
Battery Type		Lithium-ion
Battery Voltage	V	48
Battery capacity	kWh	20
	Ah	450
Indicative runtime (depending on application)	hours	up to 4
Auxiliary Battery Voltage	V	12
Auxiliary Battery capacity	Ah	70
Alternator	V/Ah	12/40
Electrical Motor		
Motor type		Permanent magnet
Motor power (peak)	kW	18
Motor power (continuous)	kW	14.8
Operating mode max. / Standard	r/min	2 050
Operating mode max. / Eco	r/min	1 800
Operating mode max. / Boost	r/min	2 400
Swing System		
Max, slew speed	r/min	9.4
Max, slew torque	daNm	485
Digging Performances		
Standard bucket width (blade, W/O side cutter)	mm	500
Standard bucket mass	kg	59
Standard bucket rated capacity	l	74
Bucket rotation	°	205
Bucket breakout force (ISO)	daN	2 233
Short arm tearout force (ISO)	daN	1 776
With short arm	mm	1 050
Long arm tearout force (ISO)	daN	1 497
With long arm	mm	1 350
Travel System		
Max, drawbar pull	daN	1 984
Max. travel speed low	km/h	2.4
Max. travel speed high	km/h	4.5
Gradeability	°	30

Hydraulic system		
Pump type		Variable displacement, load sensing
Maximum system flow	l/min	58
Maximum flow for accessories	l/min	50
Maximum pressure for accessories	MPa	25
Maximum flow for 2nd accessory circuit	l/min	23
Maximum operating pressure	MPa	25
Weight and Ground Pressure		
Operating weight according to ISO 6016	kg	2 675
Ground pressure (cab)	kPa	28.4
Transport weight	kg	2 600
With canopy		
With direct-fit bucket		
With rubber tracks	mm	300
With short arm	mm	1 050
With heated cab	+kg	90
With long arm	+kg	12
	mm	1 350
Service Refill		
Hydraulic system, total	l	33
Hydraulic tank	l	23
Travel reduction unit	l	2 x 0.6
Undercarriage		
Rubber track width	mm	300
Bottom/top rollers per side		3 / 1
Track tension		by grease piston
Blade (width x height)	mm	1 550 x 312
Sound Level		
Interior sound level according to ISO 6396		
LpA	dB	74
External sound level according to ISO 6395 and EU Noise Directive (2000/14/EC) and 474-1:2006 +A1:2009		
LwA	dB	84


VOLVO
ELECTRIC
VOLVO


Specifications




DIMENSIONS				
Description		**Unit**	**ECR25 Electric**	
Arm		**mm**	**1050**	**1350**
A	Maximum cutting height	mm	4 010	4 183
B	Maximum dump height	mm	2 784	2 957
B*	Maximum bucket clearance	mm	2 897	3 070
C	Digging depth	mm	2 461	2 761
C*	Maximum digging depth	mm	2 672	2 965
D	Maximum vertical wall digging depth	mm	1 832	2 119
E	Maximum digging reach at ground level	mm	4 313	4 602
F	Maximum digging reach	mm	4 484	4 768
G	Highest position dozer blade	mm	401	
H	Lowest position dozer blade	mm	422	
I	Tumbler length	mm	1 440	
J	Track length	mm	1 906	
K	Dozer blade, maximum reach at ground level	mm	1 365	
L	Overall width with 300 mm rubber tracks	mm	1 550	
M	Overall length	mm	4 008	3 876
M	Transport length	mm	4 595	4 525
N	Overall height of engine hood	mm	1 570	
O	Minimum ground clearance	mm	290	
P	Dozer blade height	mm	312	
Q	Shoe width (rubber)	mm	300	
R	Ground clearance to superstructure	mm	554	
S	Front slew radius	mm	2 002	
T	Front slew radius with maximum offset	mm	1 555	
U	Overall height cab	mm	2 535	
W	Overall width of superstructure	mm	1 340	
X	Tail slew radius	mm	750	
Y	Angle of approach	°	34	
Z	Dozer blade width	mm	1 550	
α_1	Maximum boom swing angle to the left	°	72	
β_1	Maximum boom offset to the right	mm	784	
α_2	Maximum boom swing angle to the right	°	56	
β_2	Maximum boom offset to the left	mm	496	

LIFTING CAPACITY ECR25 ELECTRIC

These capacities are given for a machine equipped with a cabin, 300 mm rubber tracks and without a bucket or quick coupler.
The below values are in compliance with ISO standard 10567. They do not exceed 75% of the tipping load or 87% of the hydraulic limit with the machine on firm level ground.
Loads marked with an asterisk (*) are limited by machine's hydraulic lifting capacity rather than tipping load.
Caution: In accordance with standard EN 474-5, the machine must be equipped to carry out handling operations.
It is the operator's obligation to know and follow the applicable national and local safety regulations.



Along undercarriage / Across undercarriage	Lifting point height (B)		Lifting point radius (A)									
			2.0 m			3.0 m			Max. reach			Max.
												m
Arm: 1 050 mm Counterweight: Standard	3 m	kg	-	-	-	544	567*	519	530	567*	506	3.048
	2 m	kg	-	-	-	538	600*	513	394	592*	377	3.667
	1 m	kg	-	-	-	514	797*	490	358	685*	343	3.858
	0 m	kg	904	1 602*	848	496	934*	474	374	758*	358	3.706
	-1 m	kg	914	1 546*	858	501	850*	477	471	850*	449	3.144
Arm: 1 350 mm Counterweight: Standard	2 m	kg	-	-	-	500*	500*	500*	347	508*	332	3.971
	1 m	kg	942	1 334*	884	514	715*	489	319	577*	306	4.142
	0 m	kg	894	1 608*	838	492	897*	468	330	623*	316	4.002
	-1 m	kg	897	1 659*	840	488	902*	464	397	693*	379	3.502

Equipment

STANDARD EQUIPMENT
Drivetrain
Axial piston hydraulic motors equipped with an epicyclic reduction gears
Automatic two speed travel
Bottom flanged rollers lubricated for life
Grease tensioning wheel lubricated for life
Electric / Electronic control system
Maintenance free 48V battery (3-rack) - fixed for anti-theft protection
On-board charger with Type 2 socket
Standard charger cable with 3 plugs (domestic, CEE 16A 1 phase, and CEE 32A 3 phase)
Fast charger ready with weather protected socket
Maintenance free 12V auxiliary battery
High quality connectors
Protected battery cut-off switch
Auto-idling and auto-shutdown function on electric motor
Machine exterior
Warning beacon, flashing LED
Front cabin LED worklight
Right and left rear-view mirror
High visibility orange entrance foot step and handle
White noise travel alarm
Swing System
Radial piston hydraulic motor with direct engagement on the ball internal crown wheel (no reduction gears)
Integrated shockless valve
Automatic multi-disc spring applied hydraulic released slew brake
Centralized and remote lubrication of crown wheel & ball bearing
Undercarriage
300 mm rubber tracks
“X” shape, box welded fabricated frame with sloping side members
2 Tie-down points on the dozer blade
2 Tie-down points on the frame
2 lifting points on the frame
Sturdy removeable protecting covers for track motors and slew system
400HB weld-on edge on dozer blade
Hydraulic system
Plastic tank with drain plug
Variable displacement, load-sensing piston pump
Closed centre flow-sharing main control valve
Cushioning on cylinders:
Boom up
Large tiltable oil cooler
Patented filtering and filling element
Accessory flow adjustment
Secondary relief valves for auxiliaries
Hammer / shear valve
Mineral hydraulic oil VG46
Machine control system
Finger tip control for boom offset
Finger tip control for auxiliary circuit
Breaker toggle switch on right joystick
Automatic locking device for pilot controls and travel levers when the left console is raised
Electric motor starting safety device: the left console must be raised to operate the starter
Pressure accumulator to lower the equipment on the ground when the motor is switched off
High torque / automatic two speed change over switch on the dashboard
High speed toggle switch on the dozer blade lever
Large travel pedals

STANDARD EQUIPMENT
Cab
Certified FOPS level 1 on top (Falling Object Protective Structure)
Certified TOPS (Tip-Over Protective Structure)
Certified ROPS (Roll-Over Protective Structure)
Cushioned operator station
Large door access
Large and roomy uncluttered floor
Gas-strut assisted front window opening
Full opening front bay with in-cab storage for the front lower window
Front windscreen wiper and washer nozzle
Right hand side sliding window
Flat toughened glass
Heating systems with in-cab adjustment of temperature and air flow level
Multiple adjustable air vents
Filtered air inlet
Toolbox with integrated storage for operator’s manual and lockable door.
Cab inside light
High visibility 2” orange seatbelt
Seatbelt with warning indicator
In-cab 12V power socket
Cup holder
Phone holder
Provision for a radio (antena and electric wiring already fitted)
Digging equipment
Monobloc box welded fabricated boom
Boom cylinder rod protection
Integrated lifting point on the boom
Monobloc box welded arms with casted ends
Long-life steel bushings
Hardened, pre-lubricated and corrosion resistant pins
50 hours greasing intervals
Instrumentation and monitoring
High contrast colour 5” LCD display with day and night modes enabling good readability whatever lighting conditions
Jogwheel for easy navigation and electric motor speed adjustment
3 working modes: Standard, ECO and Boost
Built-in anti-theft feature
Several warning messages, coupled to needed action, in the event of malfunction
Volvo Telematic System
Service and Maintenance
Tool Kit
Official approval
Machine conforming to European directive 2006/42/EC.
Noise emissions in the environment conforming to directive 2000/14/EC.
Hand Arm Vibrations - Whole Body Vibrations compliant with directive 2002/44/EC.
Electromagnetic compatibility (EMC) conforming to European directive 2004/108/EC and its amendments.
Object handling device conforming to EN 474-1 and EN 474-5 standards.
FOPS on top level 1 conforming to ISO 10262 standard.
TOPS conforming to ISO 12117 and EN 13531 standards.
ROPS conforming to ISO 3471-1 and / SAE J1040 standards.
OPG 1 conforming to ISO 10262 standard (when equipped).
OPG 2 conforming to ISO 10262 standard (when equipped).

OPTIONAL EQUIPMENT
Operator environment
Canopy
Heated cab
Vinyl or fabric seat, lumbar adjustment, high backrest and retractable seat belt
3” Seat Belt
ISO / SAE control pattern change
Radio AM/FM, AUX, USB, Bluetooth
Radio AM/FM/DAB, AUX, USB, SD MP3, Bluetooth
Additional lockable storage box (behind the seat)
Electric / Electronic control system
Off-board Fast charger IP54 360A – 17.3kW Outdoor
Off-board Fast charger IP21 200A – 9.6kW Indoor
Off-board Fast charger IP21 360A – 17.3kW Indoor
Machine exterior
Full LED worklights package - Front and rear of the cab, boom and rotating beacon
Several levels of paint customisation (RAL specifications) to match with your corporate identity
Green beacon linked to seat belt
Front canopy guard (OPG1)

OPTIONAL EQUIPMENT
Hydraulic system
Boom & arm safety lifting valves with overload indicator
Boom, arm and dozer blade safety lifting valves with overload indicator
Safety valve certification
Bio hydraulic oil VG46 (PANOLIN®)
Hydraulic oil VG32
Bio hydraulic oil VG32 (PANOLIN®)
Hydraulic oil VG68
Second accessory circuit
Flat face hydaulic quick couplings
Single-acting hydraulic circuit for accessories
Double-acting hydraulic circuit for accessories
Hydraulic drain for accessories
Digging equipment
Short arm 1 050 mm
Long arm 1 350 mm
Attachments
S-type mechanical quick coupler (S40)
S-type hydraulic quick coupler (S40)
Volvo quick coupler mechanical (pin-on)
Extra pin kit
Lehnhoff® Quick Coupler Mechanical (MS03)
General purpose buckets (250 mm, 34L up to 750 mm, 119L)
Aggressive cut buckets (350 mm, 50L / 550 mm, 95L)
Fix ditching buckets (1 200mm, 125 L / 1300mm, 141L)
Tiltable ditching buckets (1200 mm, 125 L)
Hydraulic breaker HB03LN

SELECTION OF VOLVO OPTIONAL EQUIPMENT


Specific colors



Secondary Accessory Circuit



Safety valves





Fast charger



Not all products are available in all markets. Under our policy of continuous improvement, we reserve the right to change specifications and design without prior notice.
The illustrations do not necessarily show the standard version of the machine.


ELECTRIC
ELECTRIC
ECR25
VOLVO
VOLVO

